



# GLD Great Light

## 80W~500W

## LED SPORTS LIGHT



### ●Product Features

1. The splicing design (patent) of aluminum die-casting modules can be customized at will, the front, rear, left and right ventilation form a good ventilation environment, which is easier to dissipate heat, and improve quality and aesthetics;
2. The dial type adjusts the angle according to the demand, and the lamp is more stable. The whole lamp adopts high-quality stainless steel 304 screws and powder baking process, which is beautiful and generous, high-strength, corrosion-resistant, and impact-resistant. It is suitable for most outdoor harsh environments;
3. The lamp adopts a unique professional light distribution design, high light transmittance, no undesirable glare, eliminates visual fatigue and line of sight interference, and improves the visual comfort of athletes. Multi-lens selection can meet a variety of lighting needs;
4. High lumen, high CRI, multi-color temperature, environmental protection, long service life, no fog or frost, soft lighting effect, protection grade IP66, suitable for different lighting environments.

### ●Applicable place

It is widely used in outdoor lighting such as stadiums, airports, large squares, ports and docks, and road



## GLD360D3-200

### ●Parameters

Model	Power(w)	Input voltage	LED ChipType	Light Efficiency	Optical Lens	CCT	CRI	PF	IEC	Size: L*W*H(mm)	IP	Working TEMP	Life
GLD360D1-80	50~80	100-305/50/60Hz	OSRAM /PHILIPS	120~180Lm/w	15°25°40°60°90°120°	2700-6000K	>70&80	≥95	Class I	392*211*68	IP65	-40℃~ + 50℃	50000H
GLD360D2-120	100~150	100-305/50/60Hz	OSRAM /PHILIPS	120~180Lm/w	15°25°40°60°90°120°	2700-6000K	>70&80	≥95	Class I	392*302*68	IP65	-40℃~ + 50℃	50000H
GLD360D3-200	150~200	100-305/50/60Hz	OSRAM /PHILIPS	120~180Lm/w	15°25°40°60°90°120°	2700-6000K	>70&80	≥95	Class I	392*393*68	IP65	-40℃~ + 50℃	50000H
GLD360D4-300	200~300	100-305/50/60Hz	OSRAM /PHILIPS	120~180Lm/w	15°25°40°60°90°120°	2700-6000K	>70&80	≥95	Class I	392*484*68	IP65	-40℃~ + 50℃	50000H
GLD360D5-350	300~400	100-305/50/60Hz	OSRAM /PHILIPS	120~180Lm/w	15°25°40°60°90°120°	2700-6000K	>70&80	≥95	Class I	392*575*68	IP65	-40℃~ + 50℃	50000H
GLD360D6-400	400~500	100-305/50/60Hz	OSRAM /PHILIPS	120~180Lm/w	15°25°40°60°90°120°	2700-6000K	>70&80	≥95	Class I	392*666*68	IP65	-40℃~ + 50℃	50000H
GLD360S6-700	700~960	100-305/50/60Hz	OSRAM /PHILIPS	120~180Lm/w	15°25°40°60°90°120°	2700-6000K	>70&80	≥95	Class I	698*666*68	IP65	-40℃~ + 50℃	50000H

### ●Points to note

1. Please use the correct power supply
2. The use of voltage can not exceed the specified range
3. Please read the product installation manual carefully before using

GLD Great Light all rights reserved. GLD Great Light does not make any representations or warranties regarding the accuracy or completeness of the information contained in this document, responsible for any actions made by this file information. The information provided in this document does not constitute any commercial agreement, nor does it form part of any quotation or contract, unless agreed by GLD.

[www.czgld-led.com](http://www.czgld-led.com)



GLD & NORTHLATITUDE66° is the trade mark of Changzhou gld photovoltaic technology co . .ltd.